

Innovative specialities for the composite industry



Gelcoat Plus



Gelcoats
High gloss surface

Bonding pastes
Powerful connections


Fire retardant systems
Optimal safety

Pigment pastes
Unlimited colours

Special products
Process solutions



BUFA®-Bond 001 Ready-to-use cartridge adhesive



Bonding Pastes

BUFA Gelcoat Plus GmbH & Co. KG
Hohe Looge 2-8
26180 Rastede
GERMANY
Phone +49 4402 975-0
Fax +49 4402 975-300
gelcoatplus@buefa.de
www.buefa.com
www.buefagelcoatplus.com


A company of BUFA and DSM Composite Resins

The information given above is based on our current state of knowledge and experience. In view of the many factors that may influence working conditions and the application of our products, the user is not relieved from carrying out his own tests and experiments. Not legally binding warranty of certain properties or suitability for a particular purpose can be derived from this information. It is the responsibility of the receiver or user of the products to observe proprietary rights as well as existing laws and regulations. The latest version of the corresponding EU safety data sheet must also be observed.

You'll find technical data sheets and further information at www.buefagelcoatplus.com.

BÜFA®-Bond 001

BÜFA®-Bond 001 is a ready-to-use cartridge adhesive based on a UP resin that is suitable for all branches. It is mainly used for joining GRP/GRP, aluminium and steel substrates, for structural bonding and fast fixation but can also be used for further special applications.



Product no.:
026-0400



Product no.:
019-0205

Sales unit:

Product no.: 660-0001 BÜFA®-Bond 001

1/1 carton

The carton contains

- 6 cartridges
- 6 static mixers
- 6 openers

Accessories:

Single: Product no.: 029-4686 Static Mixer

Package of 12: Product no.: 029-4763 Static Mixer

Directions:

Product no.: 026-0400 Hand Gun

Product no.: 019-0205 Pneumatic Gun

With the ready-to-use cartridge adhesive BÜFA®-Bond 001, high processing safety is guaranteed. Metering, mixing and application takes place in just one working operation. BÜFA®-Bond 001 cartridge adhesive is glass fibre reinforced and easy to meter. Its resistance to chemicals is outstanding, it cures tack-free, is highly thixotropic and thus has high stability. BÜFA®-Bond 001 cartridge adhesive also contains a peroxide indicator. Working temperature should range between 10 - 23 °C. The maximum application thickness of the adhesive is 7 - 8 mm.

Your Advantages:

- Ready-to-use and thus high processing safety
- Metering, mixing and application in just one working operation
- Fast, selected application of the adhesive – saves adhesive and reduces waste
- Low VOC, no opened containers, toxicologically safe
- Insensitive to fluctuations in temperature and moisture
- BP/amine curing concept
- Long shelf-life of 4 months (20 °C)